

Specifications	Product
<p>Protection Level: IP65; NEMA4X            Lifespan: &gt; 5 years.            Interface: PS2, USB available.            Supply Voltage: +5V DC +/-5%            Operating temperature: -10C to +60C.            Storage temperature: -20C to +70C.            Dimensions: 134 mm x 107 mm            Dustproof, Water proof, Vandalism resistance            Mounting type: Panel Mounting            Key switch Technology: Silicone switching element            Key switch lifetime: &gt; 5 million of operations.            Actuation Force/travel: 1N            Mounting Rack: Aluminum alloy            Lettering: laser engraved legends for excellent durability            G.W.: 0.75 kg.            Optional for Mechanical or Optical ball</p>	
Application Fields	<div style="display: flex; justify-content: space-around; align-items: center;"> <div data-bbox="890 1688 1038 1738"> <p>CE FC</p> </div> <div data-bbox="1059 1688 1219 1794"> <p>IP65 IB02</p> </div> <div data-bbox="1246 1688 1461 1832"> <p>RoHS compliant COWB1907 BOH2</p> </div> </div>
<ul style="list-style-type: none"> <li>• Self service kiosk</li> <li>• Industrial PC system</li> <li>• Medical &amp; Food industry</li> <li>• Gaming machine &amp; Vending Machine</li> <li>• Navigation &amp; aviation</li> <li>• CNC machine and other factory equipment</li> </ul>	