

Features:

- 1000 nits Sunlight Readable LCD
- Long Life, Low Power Consumption LED Backlight
- Wide Operating Temperature
- Advanced Optical Bonding (AOT)
- High Shock & Vibration Resistance
- IR Touch Support (front IP65 design)
- AR glass support (IP68 design)
- 9-36V DC Input



Specifications

Specifications	
Description	8.4" IP 68 Sunlight Readable Marine Display
Backlight	LED Backlight
Active Display Area	170.4 x 127.8 mm
Brightness	1000 cd/m ²
Resolution	800 x 600 (SVGA)
Contrast Ratio	450:1
Pixel Pitch (mm)	0.213(H) x 0.213 (V)
Viewing Angle	130 (H), 115 (V)
Display Color	16.2M
Response Time	35ms
Inputs	VGA x1
PIP Support	NA
Mechanical	
IP Rating	Waterproof IP 68 & IP 65 standards
Construction	Rugged Aluminum Alloy Chassis
Mounting	VESA mount
Dimension	250(W) x 200(H) x 64(D)
Net Weight	3 Kg
Power	
Voltage	DC Input Voltage: DC 9~36V
Power Consumption	9.5W
Environmental	
Operating Temperature	-20°C~60°C
Non-Operating Temperature	-30°C~75°C
Certification	CE / FCC
Marine Type Approval	BV Rule IACES-E10 certification, comply with IEC 60945



