

Features:

- 1000 nits Sunlight Readable LCD
 - Long Life, Low Power Consumption LED Backlight
 - -10°C~50°C Wide Operating Temperature
 - Picture in Picture Function
 - Advanced Optical Bonding (AOT)
 - High Shock & Vibration Resistance
 - Resistive Touch Support
 - IP 65 Facial Waterproof
- Outdoor Display



Specifications

Description	
Backlight	LED Backlight
Active Display Area	304.128 x 228.096 mm
Brightness	1000 cd/m ²
Resolution	1024 x 768 (XGA)
Contrast Ratio	700:1
Touch Screen	5-Wire, Analog Resistive / AR Glass
Optical	AOT
System	
Processor	Intel® Celeron™ M / Core 2 Duo Based Design
Chipset	Intel® 945GM + ICH7M
Memory	DDR II DIMM 1GB
Ethernet	Intel® 82573L 10/100/1000 Base-TX RJ 45 x2
Storage	SATA 2.5" HDD (Optional)
I/O Port	Audio Phone Jack (Line-in, Line-out, MIC-in) x1, RJ 45 x2, USB x4, COM x2 (RS232 x1, RS232/422/485 x1), DVI-I x1, VGA-out x1, KB/MS PS2 x1, Power AC-in x1
BIOS	Award
Wake on LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitor	Support power supply voltages, fan speed and temperature monitoring
Expansion Interface	Mini PCI (internal)
Power	
Voltage	AC Input: AC 100~240V; DC Input (Optional)
Power consumption	58W
Mechanical	
IP Rating	Facial waterproof to IP 65 standards when console mounted
Construction	Aluminum Alloy Chassis
Mounting	Panel (Flush) mount, VESA 75 / VESA 100, Stand Mount
Dimension	386.6(W) x 320.2(H) x 91.6(D)
Net Weight	5.4 Kg
Environmental	
Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~80°C
Operating Humidity	5~95% @ 40°C, non-condensing
Certification	Designed to meet CE / FCC



