

### Features:

- 1000 nits Sunlight Readable LCD
- Long Life, Low Power Consumption LED Backlight
- -10°C~50°C Wide Operating Temperature
- Advanced Optical Bonding (AOT)
- High Shock & Vibration Resistance
- Resistive Touch Support
- IP 65 Facial Waterproof
- Outdoor Display



### Specifications

Specifications	
<b>LCD Display</b>	
Backlight	19" LED Backlight
Active Display Area	376.32 x 301.06 mm
Brightness	1000 cd/m <sup>2</sup>
Resolution	1280 x 1024 (SXGA)
Contrast Ratio	1000:1
Touch Screen	5-Wire, Analog Resistive / AR Glass
Optical	AOT
<b>System</b>	
Processor	Intel® Celeron™ M / Core 2 Duo Based Design
Chipset	Intel® 945GM + ICH7M
Memory	DDR2 DIMM 1GB
Ethernet	Intel® 82573L 10/100/1000 Base-TX RJ 45 x2
Storage	SATA 2.5" HDD (Optional)
I/O Port	Audio Phone Jack (Line-in, Line-out, MIC-in) x1, RJ 45 x2, USB x4, COM x2 (RS232 x1, RS232/422/485 x1), DVI-I x1, VGA-out x1, KB/MS PS2 x1, Power AC-in x1
BIOS	Award
Wake on LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitor	Support power supply voltages, fan speed and temperature monitoring
Expansion Interface	Mini PCI (internal)
<b>Power</b>	
Voltage	AC Input: AC 100~240V; DC Input (Optional)
Power consumption	75W
<b>Mechanical</b>	
IP Rating	Facial waterproof to IP 65 standards when console mounted
Construction	Aluminum Alloy Chassis
Mounting	Panel (Flush) mount, VESA 75 / VESA 100, Stand Mount
Dimension	447(W) x 390.6(H) x 91.5(D)
Net Weight	7.2 Kg
<b>Environmental</b>	
Operating Temperature	-10°C~40°C
Storage Temperature	-20°C~80°C
Operating Humidity	5~95% @ 40°C, non-condensing
Certification	Designed to meet CE / FCC



