

Features:

- 1600 nits Sunlight Readable LCD
 - Long Life, Low Power Consumption LED Backlight
 - Advanced Optical Bonding (AOT)
 - 0°C~50°C Operating Temperature
 - High Shock & Vibration Resistance
 - PCT Multi-Touch Support
 - IP 65 Facial Waterproof
- Outdoor Display



Specifications

Description	
Backlight	19" LED Backlight
Active Display Area	377.32 x 302.06 mm
Brightness	1600 cd/m ²
Resolution	1280 x 1024 (SXGA)
Contrast Ratio	1000:1
Touch Screen	PCT Multi-Touch
Optical	AOT
System	
Processor	Intel® Core™ i5
Chipset	Intel® H81 Express Chipset
Memory	DDR3 SO DIMM 4GB
Ethernet	Realtek 8111F PCIe Gigabit LAN
Storage	SATA 2.5" HDD (Optional)
I/O Port	RJ 45 x2, USB 3.0 x2, USB 2.0 x4, COM x2, DVI x1, VGA x1, Audio Jack x2 (Mic-in, Line-out), PS2 x1 (KB & Mouse), Power AC-in x1
BIOS	AMI
Wake on LAN	Yes
Watchdog Timer	1~255 steps programmable
H/W Status Monitor	Support power supply voltages, fan speed and temperature monitoring
Expansion Interface	Mini PCIe (internal)
Power	
Voltage	AC Input: AC 100~240V; DC Input (Optional)
Power consumption	90W
Mechanical	
IP Rating	Facial waterproof to IP 65 standards when console mounted
Construction	Aluminum Alloy Chassis
Mounting	Panel (Flush) mount, VESA 75 / VESA 100, Stand Mount
Dimension	469.5(W) x 427.35(H) x 92.2(D)
Net Weight	5.5 Kg
Environmental	
Operating Temperature	0°C~50°C
Storage Temperature	-20°C~60°C
Operating Humidity	5~95% @ 40°C, non-condensing
Certification	Designed to meet CE / FCC



