

RACK



Model Name	RACK-407SE-1312
System	
CPU	Intel® 9th/ 8th Gen (Coffee Lake-S) Core™ Processors, up to 95W
Speed	3.4 Ghz 3.4 GHz 3.0 GHz 3.1 GHz 3.3 GHz 3.3 GHz 3.1 GHz 2.9 GHz 2.5 GHz
Chipset	Intel® Q370
RAM	Dual Channel DDR4 2666 MHz 128GB* 4x 288-pin Long-DIMM
Operative System	Windows® XP 7 10
Graphics	
Controller	Coffee Lake integrated graphics
MultiDisplay	Triple Display
Input / Output	
VGA	1x
DVI	1x
Ethernet	2x RJ-45 (1x Intel® I210 1x Intel® I219LM
USB	Rear 4x USB 3.1 (Gen1) Internal 2x USB 3.1 (Gen1) (1 x USB3.1 header) 6x USB 2.0 (3x 2.54 pitch header)
Serial	Rear COM1(RS-232/422/485) Internal COM2, 3, 4, 5, 6 (RS-232)
PS/2	1x
Expansion Slots	
PCIe	2x PCIe 3.0 x16 Slots (PCIe1/PCIe3: single at x16 (PCIe1) dual at x8 (PCIe1) / x8 (PCIe3)) 2x PCIe 3.0 x4 Slots (PCIe2) (PCIe4)
mini-PCIe	1 x Full/Half size with PCIe x1 and USB 2.0
Mechanical	
Housing	SGCC
Mounting	4x Units Rack Mounting
Dimensions	430mm (W) x 176mm (H) x 469mm (D)
Net Weight	10.8 kg
Environmental	
Power Input	230 V 110V / 500W Default
Operating Temperature	0 ~ 55° C
Storage Temperature	-40 ~ 85° C
Conformity	
Certifications	CE

