

# RACK



Model Name	RACK-407SE-785
<b>System</b>	
CPU	-Intel® Core™ i7-7700   i7-7700T   i7-6700   i7-6700TE   i5-7500   i5-7500T   i5-6500   i5-6500TE   i3-7101E   i3-7101TE   i3-6100   i3-6100TE   G4400   G4400TE   G3900   G3900TE
Speed	3.6 GHz   2.9 GHz   3.4 GHz   2.4 GHz   3.4 GHz   2.7 GHz   3.2 GHz   2.3 GHz   3.9 GHz   3.4GHz   3.7 GHz   2.7 GHz   3.3 GHz   2.9 GHz   2.8 GHz   2.6 GHz
Chipset	Q170
RAM	Dual Channel DDR4 1866/2133 64 GB 4 x 288-pin DIMM
Operative System	Windows® XP   7   10
<b>Graphics</b>	
Controller	Intel HD Graphics
VRAM	1 GB maximum shared memory with 2 GB and above system memory installed
<b>Input / Output</b>	
VGA	1x
DVI	2x
Ethernet	2x RJ-45, GbE LAN1: Intel I219LM, GbE LAN2: Intel I211AT
USB	Rear 6x (USB3.0 x 4, USB2.0 x 2)   Internal 7x (USB 3.0 with wafer box x 2, USB 2.0 with wafer box x 4, USB 2.0 with type A connector x 1)
Serial	Rear 1x (RS-232)   Internal 5x (4 x RS-232, 1 x RS-232/422/485)
PS/2	1x (Optional PS/2 KB/Mouse Cable is required)
<b>Expansion Slots</b>	
PCIe	3x slots PCI 32-bit/33 MHz
PCIe x 4 (Gen3)	3x 4 GB/s per direction
PCIe x16 (Gen3)	1x 16 GB/s per direction
<b>Mechanical</b>	
Housing	SGCC
Mounting	4x Units Rack Mounting
Dimensions	430mm (W) x 176mm (H) x 469mm (D)
Net Weight	10.8 kg
<b>Environmental</b>	
Power Input	230 V   110V / 500W Default
Operating Temperature	0 ~ 55° C
Storage Temperature	-40 ~ 85° C
<b>Conformity</b>	
Certifications	CE

