

SLIM 918



System

- CPU	Intel® 7th & 6th Gen Core™ i processor (LGA1151) i7-6700TE/i5-6500TE/Pentium 4400TE
- Chipset	Intel Q170
- Memory type	Dual Channel DDR4 2133MHz SDRAM MAX 32GB
- Ethernet	GbE LAN1: Intel i219LM; LAN2: Intel i211AT

I/O

- Serial ports	1 x RS232, 1 x RS232/422/485
- USB ports	4 USB 3.0 + 2 USB 2.0 (optional)
- Audio	3 (Mic-in, Line-out, Line-in)
- Video input	1 VGA - 1 HDMI - 1 DP
- Ethernet	2 x RJ45
- Power connection	1 x 4 pin DC terminal block 1 x 2 pin remote power switch 2 x LED light for power and HDD indication

Storage Space

- HDD	2 x 2,5" SATA3 (Support RAID 0,1) easily accessible design
- Mini-PCIe	1 x mSATA slot (full-size)
- M2	B key for SSD and 3G supported (type: 2242 ,2280mm)

Expansion Slot

-Mini-PCIe	1, F/S Mini-PCIe slot (with mSATA supported)
-PCIe	2 PCIe 8X or 3 PCI (optional)

Environment

Operating temperature	0 __ 50 °C
Storage temperature	-30 __ 70 °C
Storage humidity	10 to 90% @ 40 °C - non condensing
Certification	CE

Display

- Display type	18,5" TFT-LCD
- Max. resolution	1366 x 768
- Max. color	16,7 M
- Luminance (cd/m2)	300
- View angle (H°/V°)	85 __ 85 (H) 80 __ 80 (V)
- Contrast	1000 : 1

Touch Screen

- Type	Project capacitive
- Interface	USB
- Light transmission	Project capacitive: 90%

Mechanical


- Construction	Aluminum front bezel optional INOX 316
- IP Rating	Front bezel IP65
- Mounting	Panel mounting
- Dimension (mm)	536 x 380 x 116
- Net weight	-

Supported Operating System


- Windows 7 Professional (32/64bit)
- Windows 7 Ultimate (32/64bit)
- Windows 7 Embedded (32/64bit)
- Windows 10 IoT Enterprise (32/64bit)
- Linux

Technical Features



- It can support two different TFT with full HD or HD resolution




Legenda




- A/B/C/D: USB 2.0 (opt)
- E: POWER BUTTON
- F: COM 1
- G: COM 2
- H: COM 3 (opt)
- I: COM 4 (opt)
- L: COM 5 (opt)
- M: COM 6 (opt)
- N: HD 1
- O: HD 2
- P: DC INPUT 12-24V
- Q: VGA
- R: DP1++
- S: HDMI
- T: ETH 1
- U: ETH 2
- V: ETH 3
- Z: ETH 4
- 1: USB 3.0 1-2
- 2: USB 3.0 3-4



364 (CUTOUT)



only version with 3 slots PCI



unit: mm

