

SLIM-918 FN4



Model N°	SLIM-918 FN4
System	
CPU	Intel® 4th Gen. Core™ i5/i3 Processor
Memory Type	Single Channel DDR3L 1333/1600MHz SDRAM 8GB
Ethernet	GbE LAN1: RTL 8111G; LAN2: Intel® I218LM
I/O	
Serial	2x RS232, 2x RS232/422/485
USB	4x USB 3.0, 4x USB 2.0
Audio	/
Graphics	2x HDMI, 1x LVDS, Triple Display
Ethernet	2x RJ45
Storage Space	
HDD	2x 2,5" SATA3 easily accessible design
Expansion Slot	
Mini-PCIe	1x half with PCIe x1 and USB 2.0
mSATA	1x SATA2
Environment	
Operating Temperature	0 ~ 60°C
Storage Temperature	-40 ~ 85°C
Storage Humidity	10 to 90% @ 40°C non-condensing
Certification	CE
Display	
Display type	18.5" TFT-LCD 16:9
Max. resolution	1366 x 768 / 1920 x 1080 (optional full HD)
Max. color	16,7 M
Luminance (cd/m2)	300
View Angle (H°/V°)	85 / 85 (H) 80 / 80 (V)
Contrast	1000:1
Touch Screen	
Type	Projected Capacitive
Interface	USB
Light transmission	Projected Capacitive: 90% / Resistive: 80%
Mechanical	
Construction	Aluminum front bezel / INOX 316 (optional)
IP rating	IP 66
Mounting	Panel mounting
Dimension (mm)	536 x 380 x 81
Net weight	7 Kg
Supported Operating System	
Windows®	Windows® 7 PRO, 7 Ultimate, WS7E, WS7P, 10 PRO, 10 IoT / Linux
Ordering Information	
Models	SLIM-918P FN4-i3 SLIM-918P FN4-i5

Legenda

▣ > full HD (inserted in the code as a final letter) - es HS-2528F
 ▣ > INOX 316 (inserted in the code as a final letter) - es HS-2528P JX

Legenda



- A: HD
- B: POWER BUTTON
- C: DC INPUT 9-36V
- D: ETH 1/2
- E: HDMI 1/2
- F: USB 3.0
- G: GROUNDING

SLIM 9 18 P FN 4 i5

PC series

class number

display size

touch screen

fanless

generation N°

processor

i3

i5

P (Capacitive)

Dimensions

