

# SLIM-921 FN4



Model N°	<b>SLIM-921 FN4</b>
<b>System</b>	
CPU	Intel® 4th Gen. Core™ i5/i3 Processor
Memory Type	Single Channel DDR3L 1333/1600MHz SDRAM 8GB
Ethernet	GbE LAN1: RTL 8111G; LAN2: Intel® I218LM
<b>I/O</b>	
Serial	2x RS232, 2x RS232/422/485
USB	4x USB 3.0, 5x USB 2.0 (1x front)
Audio	/
Graphics	2x HDMI, 1x LVDS, Triple Display
Ethernet	2x RJ45
<b>Storage Space</b>	
HDD	2x 2,5" SATA3 easily accessible design
<b>Expansion Slot</b>	
Mini-PCIe	1x half with PCIe x1 and USB 2.0
mSATA	1x SATA2
<b>Environment</b>	
Operating Temperature	0 ~ 60°C
Storage Temperature	-40 ~ 85°C
Storage Humidity	10 to 90% @ 40°C non-condensing
Certification	CE
<b>Display</b>	
Display type	21.5" TFT-LCD 16:9
Max. resolution	1920 x 1080
Max. color	16,7 M
Luminance (cd/m2)	300
View Angle (H°/V°)	89 / 89 (H) 89 / 89 (V)
Contrast	5000:1
<b>Touch Screen</b>	
Type	Projected Capacitive
Interface	USB
Light transmission	Projected Capacitive: 90% / Resistive: 80%
<b>Mechanical</b>	
Construction	Aluminum front bezel / INOX 316 (optional)
IP rating	IP 66
Mounting	Panel mounting
Dimension (mm)	572 x 396 x 86
Net weight	8 Kg
<b>Supported Operating System</b>	
Windows®	Windows® 7 PRO, 7 Ultimate, WS7E, WS7P, 10 PRO, 10 IoT / Linux
<b>Ordering Information</b>	
Models	<b>SLIM-921P FN4-i3</b> <b>SLIM-921P FN4-i5</b>
Legenda	☒ › INOX 316 (inserted in the code as a final letter) - es HS-2528P JX

### Legenda



- A: HD
- B: POWER BUTTON
- C: DC INPUT 9-36V
- D: ETH 1/2
- E: HDMI 1/2
- F: USB 3.0
- G: GROUNDING

SLIM 9 21 P FN 4 i5

PC series

class number

display size

touch screen

fanless

generation N°

processor

i3

i5

P (Capacitive)

### Dimensions

