

Features

- Wallmount Fanless Enclosure
- For MICRO ATX Motherboard with CPU TDP 60W max
- Support 4x Expansion slot
- 2.5" HDD Serial ATA Tray x2 (Full Height)
- Adjustable heat pipe provides excellent compatibility






Technical data

- Input voltage 24V DC (22.5 / 28V)
- Input current 6.7 A max.
- Output voltage In normal mode: app. 0.5V below input voltage __ In battery mode: app. 29 / 19V DC
- Output current 6 A max.
- Battery charge current 0.65 A max. (internal battery charger)
- Charging method UI characteristic, with temperature regulation
- Protection Deep discharge protection: 19V DC +/-2% __ Overload protection at output: 9 A for 2 seconds, switch off
Short-circuit protection: switch off via μ C
- Transfer time/limits Mains/battery 20V DC +/-2% battery/mains 22V DC +/-2%
- Interface USB (Standard B)
- Type of battery Equipped lead-gel-battery, maintenance-free, 1.3 Ah
- Safety/EMC CE
- Temperature Operating: 0~+40°C / Storage: -10~+40°C
- Humidity Operating: 10~85% RH, non-condensing __ Storage: 10~90% RH, non-condensing
- Dimensions 90 x 100 x 121 +/-0.5 mm
- Weight 2 Kg

Product specific data

- LED display 3 colour LED for Power ok (green), Power fail (orange), Battery low (red/orange flashing) and Battery defect (red/green flashing), short circuit at output/overload (red)
- Battery monitoring Battery test is carried out in normal mode approx every 10 minutes, in case of Battery defect notification the LED flashes red/green
- Power consumption App. 80 mA
- Shutdown detection Via UPS software, UPSI Control Center
- Shutdown-suppression During system start-up the shutdown signal is suppressed for app. 2 minutes
- Reboot function If power fails and then returns during the shutdown mode of Windows®, the operating system will lock with the message, your PC is now safe. The reboot function restarts the system after about 10 sec.
- Load sensor Adjustable via UPS software, UPSI Control Center. When falling below the set load the UPS switches off after 5 seconds
- Timer function Adjustable via UPS software, UPSI Control Center in 2 minutes-step from 2/20 min.
- Back up time App. 33 min at 1 A / app. 9 min at 3 A / app. 3.5 min at 5 A (measured at +20°C)
- UPS software UPSI Control Center (Windows® XP or higher)



2 internal batteries
12V / 1.3 Ah

5 years
delivery

Fanless

Premium

24 / 7
operation

UNIT: mm